

MiCable



高达
600W CW

0.3~18GHz

大功率单/双定向耦合器

🔍 产品选型指南

福建迈可博电子科技集团股份有限公司

www.micable.cn

大功率单定向/双定向耦合器快速查询表

工作频段 (GHz)	耦合度 (dB)	30				40			
		120W	250W	400W	600W	120W	250W	400W	600W
0.3~6		●	●	●	●	●	●	●	●
0.3~8		●	●	●	●	●	●	●	●
0.4~6		●	●	●	●	●	●	●	●
0.4~8		●	●	●	●	●	●	●	●
0.5~6		●	●	●	●	●	●	●	●
0.5~8		●	●	●	●	●	●	●	●
0.5~18		●	●	●		●	●	●	
0.7~6		●	●	●	●	●	●	●	●
0.7~8		●	●	●	●	●	●	●	●
0.7~18		●	●	●		●	●	●	
1~6		●	●	●	●	●	●	●	●
1~8		●	●	●	●	●	●	●	●
1~18		●	●	●		●	●	●	
2~6		●	●	●	●	●	●	●	●
2~8		●	●	●	●	●	●	●	●
2~18		●	●	●		●	●	●	
6~18		●	●	●		●	●	●	

大功率单定向耦合器常规型号及技术指标

工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
		Max.(W)	(dB)	Max.(1)	Max.(1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
0.3~6	D3002H003060	120	30	1.3	1.3	0.8	30±1.0	±0.9	18	173×17.5×23
	D4002H003060	120	40	1.3	1.3	0.8	40±1.0	±0.9	18	173×17.5×23
	D3005H003060	250	30	1.4	1.4	0.6	30±0.9	±1.2	15	211.9×20×35
	D4005H003060	250	40	1.4	1.4	0.6	40±1.0	±1.3	15	211.9×20×35
	D3008H003060	400	30	1.4	1.4	0.6	30±0.9	±1.2	15	217.9×30×43.4
	D4008H003060	400	40	1.4	1.4	0.6	40±1.0	±1.3	15	217.9×30×43.4
	D3012H003060	600	30	1.4	1.4	0.6	30±0.9	±1.2	15	217.9×30×43.4
	D4012H003060	600	40	1.4	1.4	0.6	40±1.0	±1.3	15	217.9×30×43.4
0.3~8	D3002H003080	120	30	1.3	1.3	0.9	30±1.0	±0.9	18	173×17.5×23
	D4002H003080	120	40	1.3	1.3	0.9	40±1.0	±0.9	18	173×17.5×23
	D3005H003080	250	30	1.4	1.4	0.7	30±1.0	±1.3	14	211.9×20×35
	D4005H003080	250	40	1.4	1.4	0.7	40±1.1	±1.4	14	211.9×20×35
	D3008H003080	400	30	1.4	1.4	0.7	30±1.0	±1.3	14	217.9×30×43.4
	D4008H003080	400	40	1.4	1.4	0.7	40±1.1	±1.4	14	217.9×30×43.4
	D3012H003080	600	30	1.4	1.4	0.7	30±1.0	±1.3	14	217.9×30×43.4
	D4012H003080	600	40	1.4	1.4	0.7	40±1.1	±1.4	14	217.9×30×43.4
0.4~6	D3002H004060	120	30	1.3	1.3	0.7	30±1.0	±0.8	18	139.7×17.5×23
	D4002H004060	120	40	1.3	1.3	0.7	40±1.0	±0.8	18	139.7×17.5×23
	D3005H004060	250	30	1.3	1.3	0.6	30±0.8	±1.2	15	181.5×20×35
	D4005H004060	250	40	1.3	1.3	0.6	40±0.9	±1.3	15	181.5×20×35
	D3008H004060	400	30	1.3	1.3	0.6	30±0.8	±1.2	15	187.5×30×43.4
	D4008H004060	400	40	1.3	1.3	0.6	40±0.9	±1.3	15	187.5×30×43.4
	D3012H004060	600	30	1.3	1.3	0.6	30±0.8	±1.2	15	187.5×30×43.4
	D4012H004060	600	40	1.3	1.3	0.6	40±0.9	±1.3	15	187.5×30×43.4
0.4~8	D3002H004080	120	30	1.3	1.3	0.8	30±1.0	±0.8	18	139.7×17.5×23
	D4002H004080	120	40	1.3	1.3	0.8	40±1.0	±0.8	18	139.7×17.5×23
	D3005H004080	250	30	1.4	1.4	0.7	30±0.9	±1.3	14	181.5×20×35
	D4005H004080	250	40	1.4	1.4	0.7	40±1.0	±1.4	14	181.5×20×35
	D3008H004080	400	30	1.4	1.4	0.7	30±0.9	±1.3	14	187.5×30×43.4
	D4008H004080	400	40	1.4	1.4	0.7	40±1.0	±1.4	14	187.5×30×43.4
	D3012H004080	600	30	1.4	1.4	0.7	30±0.9	±1.3	14	187.5×30×43.4
	D4012H004080	600	40	1.4	1.4	0.7	40±1.0	±1.4	14	187.5×30×43.4
0.5~6	D3002H005060	120	30	1.3	1.3	0.6	30±1.0	±0.7	18	111.8×17.5×23
	D4002H005060	120	40	1.3	1.3	0.6	40±1.0	±0.7	18	111.8×17.5×23
	D3005H005060	250	30	1.3	1.3	0.4	30±0.7	±1.0	15	168.8×20×35
	D4005H005060	250	40	1.3	1.3	0.4	40±0.8	±1.1	15	168.8×20×35
	D3008H005060	400	30	1.3	1.3	0.4	30±0.7	±1.0	15	174.8×30×43.4
	D4008H005060	400	40	1.3	1.3	0.4	40±0.8	±1.1	15	174.8×30×43.4
	D3012H005060	600	30	1.3	1.3	0.4	30±0.7	±1.0	15	174.8×30×43.4
	D4012H005060	600	40	1.3	1.3	0.4	40±0.8	±1.1	15	174.8×30×43.4
0.5~8	D3002H005080	120	30	1.3	1.3	0.7	30±1.0	±0.7	16	111.8×17.5×23
	D4002H005080	120	40	1.3	1.3	0.7	40±1.0	±0.7	16	111.8×17.5×23
	D3005H005080	250	30	1.4	1.4	0.5	30±0.8	±1.1	14	168.8×20×35
	D4005H005080	250	40	1.4	1.4	0.5	40±0.9	±1.2	14	168.8×20×35
	D3008H005080	400	30	1.4	1.4	0.5	30±0.8	±1.1	14	174.8×30×43.4
	D4008H005080	400	40	1.4	1.4	0.5	40±0.9	±1.2	14	174.8×30×43.4
	D3012H005080	600	30	1.4	1.4	0.5	30±0.8	±1.1	14	174.8×30×43.4
	D4012H005080	600	40	1.4	1.4	0.5	40±0.9	±1.2	14	174.8×30×43.4
0.5~18	D3002H005180	120	30	1.5	1.6	1.0	30±1.2	±1.2	10	168.8×20×35
	D4002H005180	120	40	1.5	1.6	1.0	40±1.2	±1.4	10	168.8×20×35

*包含理论耦合损耗

工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
		Max.(W)	(dB)	Max.(:1)	Max.(:1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
0.5~18	D3005H005180	250	30	1.5	1.6	1.0	30±1.2	±1.2	10	168.8×20×35
	D4005H005180	250	40	1.5	1.6	1.0	40±1.2	±1.4	10	168.8×20×35
	D3008H005180	400	30	1.5	1.6	1.0	30±1.2	±1.2	10	174.8×30×43.4
	D4008H005180	400	40	1.5	1.6	1.0	40±1.2	±1.4	10	174.8×30×43.4
0.7~6	D3002H007060	120	30	1.3	1.3	0.6	30±0.9	±0.7	18	111.8×17.5×23
	D4002H007060	120	40	1.3	1.3	0.5	40±0.9	±0.7	18	111.8×17.5×23
	D3005H007060	250	30	1.3	1.3	0.4	30±0.7	±0.9	15	138.3×20×35
	D4005H007060	250	40	1.3	1.3	0.4	40±0.7	±0.9	15	138.3×20×35
	D3008H007060	400	30	1.3	1.3	0.4	30±0.7	±0.9	15	144.3×30×43.4
	D4008H007060	400	40	1.3	1.3	0.4	40±0.7	±0.9	15	144.3×30×43.4
	D3012H007060	600	30	1.3	1.3	0.4	30±0.7	±0.9	15	144.3×30×43.4
	D4012H007060	600	40	1.3	1.3	0.4	40±0.7	±0.9	15	144.3×30×43.4
0.7~8	D3002H007080	120	30	1.3	1.3	0.7	30±0.9	±0.7	16	111.8×17.5×23
	D4002H007080	120	40	1.3	1.3	0.7	40±0.9	±0.7	16	111.8×17.5×23
	D3005H007080	250	30	1.4	1.4	0.5	30±0.8	±1.0	14	138.3×20×35
	D4005H007080	250	40	1.4	1.4	0.5	40±0.8	±1.0	14	138.3×20×35
	D3008H007080	400	30	1.4	1.4	0.5	30±0.8	±1.0	14	144.3×30×43.4
	D4008H007080	400	40	1.4	1.4	0.5	40±0.8	±1.0	14	144.3×30×43.4
	D3012H007080	600	30	1.4	1.4	0.5	30±0.8	±1.0	14	144.3×30×43.4
	D4012H007080	600	40	1.4	1.4	0.5	40±0.8	±1.0	14	144.3×30×43.4
0.7~18	D3002H007180	120	30	1.5	1.6	0.9	30±1.2	±1.1	10	138.3×20×35
	D4002H007180	120	40	1.5	1.6	0.9	40±1.2	±1.2	10	138.3×20×35
	D3005H007180	250	30	1.5	1.6	0.9	30±1.2	±1.1	10	138.3×20×35
	D4005H007180	250	40	1.5	1.6	0.9	40±1.2	±1.2	10	138.3×20×35
	D3008H007180	400	30	1.5	1.6	0.9	30±1.2	±1.1	10	144.3×30×43.4
	D4008H007180	400	40	1.5	1.6	0.9	40±1.2	±1.2	10	144.3×30×43.4
1~6	D3002H010060	120	30	1.3	1.3	0.5	30±0.8	±0.5	18	88.9×17.5×23
	D4002H010060	120	40	1.3	1.3	0.5	40±0.8	±0.5	18	88.9×17.5×23
	D3005H010060	250	30	1.3	1.3	0.4	30±0.7	±0.9	15	101.6×20×35
	D4005H010060	250	40	1.3	1.3	0.4	40±0.7	±0.9	15	101.6×20×35
	D3008H010060	400	30	1.3	1.3	0.4	30±0.7	±0.9	15	107.6×30×43.4
	D4008H010060	400	40	1.3	1.3	0.4	40±0.7	±0.9	15	107.6×30×43.4
	D3012H010060	600	30	1.3	1.3	0.4	30±0.7	±0.9	15	107.6×30×43.4
	D4012H010060	600	40	1.3	1.3	0.4	40±0.7	±0.9	15	107.6×30×43.4
1~8	D3002H010080	120	30	1.3	1.3	0.6	30±0.8	±0.5	18	88.9×17.5×23
	D4002H010080	120	40	1.3	1.3	0.6	40±0.8	±0.5	18	88.9×17.5×23
	D3005H010080	250	30	1.4	1.4	0.4	30±0.8	±0.9	14	101.6×20×35
	D4005H010080	250	40	1.4	1.4	0.4	40±0.8	±0.9	14	101.6×20×35
	D3008H010080	400	30	1.4	1.4	0.4	30±0.8	±0.9	14	107.6×30×43.4
	D4008H010080	400	40	1.4	1.4	0.4	40±0.8	±0.9	14	107.6×30×43.4
	D3012H010080	600	30	1.4	1.4	0.4	30±0.8	±0.9	14	107.6×30×43.4
	D4012H010080	600	40	1.4	1.4	0.4	40±0.8	±0.9	14	107.6×30×43.4
1~18	D3002H010180	120	30	1.5	1.6	0.6	30±1.2	±1.0	10	101.6×20×35
	D4002H010180	120	40	1.5	1.6	0.6	40±1.2	±1.0	10	101.6×20×35
	D3005H010180	250	30	1.5	1.6	0.6	30±1.2	±1.0	10	101.6×20×35
	D4005H010180	250	40	1.5	1.6	0.6	40±1.2	±1.0	10	101.6×20×35
	D3008H010180	400	30	1.5	1.6	0.6	30±1.2	±1.0	10	107.6×30×43.4
	D4008H010180	400	40	1.5	1.6	0.6	40±1.2	±1.0	10	107.6×30×43.4
2~6	D3002H020060	120	30	1.3	1.3	0.4	30±0.8	±0.5	18	57.2×17.5×23
	D4002H020060	120	40	1.3	1.3	0.4	40±0.8	±0.5	18	57.2×17.5×23
	D3005H020060	250	30	1.3	1.3	0.4	30±0.7	±0.7	15	80.7×20×35
	D4005H020060	250	40	1.3	1.3	0.4	40±0.7	±0.7	15	80.7×20×35

*包含理论耦合损耗

	工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
			Max.(W)	(dB)	Max.(:1)	Max.(:1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
大 功 率 单 定 向 耦 合 器	2~6	D3008H020060	400	30	1.3	1.3	0.4	30±0.7	±0.7	15	86.7×30×43.4
		D4008H020060	400	40	1.3	1.3	0.4	40±0.7	±0.7	15	86.7×30×43.4
		D3012H020060	600	30	1.3	1.3	0.4	30±0.7	±0.7	15	86.7×30×43.4
		D4012H020060	600	40	1.3	1.3	0.4	40±0.7	±0.7	15	86.7×30×43.4
	2~8	D3002H020080	120	30	1.3	1.3	0.5	30±0.8	±0.5	18	57.2×17.5×23
		D4002H020080	120	40	1.3	1.3	0.5	40±0.8	±0.5	18	57.2×17.5×23
		D3005H020080	250	30	1.4	1.4	0.4	30±0.8	±0.7	14	80.7×20×35
		D4005H020080	250	40	1.4	1.4	0.4	40±0.8	±0.7	14	80.7×20×35
		D3008H020080	400	30	1.4	1.4	0.4	30±0.8	±0.7	14	86.7×30×43.4
		D4008H020080	400	40	1.4	1.4	0.4	40±0.8	±0.7	14	86.7×30×43.4
		D3012H020080	600	30	1.4	1.4	0.4	30±0.8	±0.7	14	86.7×30×43.4
		D4012H020080	600	40	1.4	1.4	0.4	40±0.8	±0.7	14	86.7×30×43.4
		D5012H020080	600	50	1.4	1.4	0.4	50±1.5	±1.2	14	86.7×30×43.4
		2~18	D3002H020180	120	30	1.5	1.6	0.6	30±1.0	±0.8	10
	D4002H020180		120	40	1.5	1.6	0.6	40±1.0	±0.8	10	80.7×20×35
	D3005H020180		250	30	1.5	1.6	0.6	30±1.0	±0.8	10	80.7×20×35
	D4005H020180		250	40	1.5	1.6	0.6	40±1.0	±0.8	10	80.7×20×35
	D3008H020180		400	30	1.5	1.6	0.6	30±1.0	±0.8	10	86.7×30×43.4
	D4008H020180		400	40	1.5	1.6	0.6	40±1.0	±0.8	10	86.7×30×43.4
	D5008H020180		400	50	1.5	1.6	0.6	50±2.0	±1.5	10	86.7×30×43.4
	6~18		D3002H060180	120	30	1.5	1.6	0.5	30±1.0	±0.7	10
		D4002H060180	120	40	1.5	1.6	0.5	40±1.0	±0.7	10	69.7×20×35
		D3005H060180	250	30	1.5	1.6	0.5	30±1.0	±0.7	10	69.7×20×35
		D4005H060180	250	40	1.5	1.6	0.5	40±1.0	±0.7	10	69.7×20×35
		D3008H060180	400	30	1.5	1.6	0.5	30±1.0	±0.7	10	75.7×30×43.4
		D4008H060180	400	40	1.5	1.6	0.5	40±1.0	±0.7	10	75.7×30×43.4

*包含理论耦合损耗

大功率双定向耦合器常规型号及技术指标

	工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
			Max.(W)	(dB)	Max.(:1)	Max.(:1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
大 功 率 双 定 向 耦 合 器	0.3~6	D3002HB003060	120	30	1.3	1.3	0.8	30±1.0	±1.1	18	173×17.5×30
		D4002HB003060	120	40	1.3	1.3	0.8	40±1.0	±1.1	18	173×17.5×30
		D3005HB003060	250	30	1.4	1.4	0.7	30±0.9	±1.5	15	211.9×20×45
		D4005HB003060	250	40	1.4	1.4	0.7	40±1.0	±1.6	15	211.9×20×45
		D3008HB003060	400	30	1.4	1.4	0.7	30±0.9	±1.5	15	225.9×25.4×47.5
		D4008HB003060	400	40	1.4	1.4	0.7	40±1.0	±1.6	15	225.9×25.4×47.5
		D3012HB003060	600	30	1.4	1.4	0.7	30±0.9	±1.5	15	225.9×25.4×47.5
		D4012HB003060	600	40	1.4	1.4	0.7	40±1.0	±1.6	15	225.9×25.4×47.5
	0.3~8	D3002HB003080	120	30	1.3	1.3	0.9	30±1.0	±1.1	18	173×17.5×30
		D4002HB003080	120	40	1.3	1.3	0.9	40±1.0	±1.1	18	173×17.5×30
		D3005HB003080	250	30	1.4	1.4	0.8	30±1.0	±1.6	14	211.9×20×45
		D4005HB003080	250	40	1.4	1.4	0.8	40±1.1	±1.7	14	211.9×20×45
		D3008HB003080	400	30	1.4	1.4	0.8	30±1.0	±1.6	14	225.9×25.4×47.5
		D4008HB003080	400	40	1.4	1.4	0.8	40±1.1	±1.7	14	225.9×25.4×47.5
		D3012HB003080	600	30	1.4	1.4	0.8	30±1.0	±1.6	14	225.9×25.4×47.5
		D4012HB003080	600	40	1.4	1.4	0.8	40±1.1	±1.7	14	225.9×25.4×47.5
	0.4~6	D3002HB004060	120	30	1.3	1.3	0.7	30±1.0	±1.0	18	139.7×17.5×30
		D4002HB004060	120	40	1.3	1.3	0.7	40±1.0	±1.0	18	139.7×17.5×30
		D3005HB004060	250	30	1.3	1.3	0.6	30±0.8	±1.4	15	181.5×20×45
		D4005HB004060	250	40	1.3	1.3	0.6	40±0.9	±1.5	15	181.5×20×45
		D3008HB004060	400	30	1.3	1.3	0.6	30±0.8	±1.4	15	195.5×25.4×47.5
		D4008HB004060	400	40	1.3	1.3	0.6	40±0.9	±1.5	15	195.5×25.4×47.5
		D3012HB004060	600	30	1.3	1.3	0.6	30±0.8	±1.4	15	195.5×25.4×47.5
		D4012HB004060	600	40	1.3	1.3	0.6	40±0.9	±1.5	15	195.5×25.4×47.5

*包含理论耦合损耗

工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
		Max.(W)	(dB)	Max.(:1)	Max.(:1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
0.4~8	D3002HB004080	120	30	1.3	1.3	0.8	30±1.0	±1.0	18	139.7×17.5×30
	D4002HB004080	120	40	1.3	1.3	0.8	40±1.0	±1.0	18	139.7×17.5×30
	D3005HB004080	250	30	1.4	1.4	0.7	30±0.9	±1.5	14	181.5×20×45
	D4005HB004080	250	40	1.4	1.4	0.7	40±1.0	±1.6	14	181.5×20×45
	D3008HB004080	400	30	1.4	1.4	0.7	30±0.9	±1.5	14	195.5×25.4×47.5
	D4008HB004080	400	40	1.4	1.4	0.7	40±1.0	±1.6	14	195.5×25.4×47.5
	D3012HB004080	600	30	1.4	1.4	0.7	30±0.9	±1.5	14	195.5×25.4×47.5
	D4012HB004080	600	40	1.4	1.4	0.7	40±1.0	±1.6	14	195.5×25.4×47.5
0.5~6	D3002HB005060	120	30	1.3	1.3	0.6	30±1.0	±1.0	18	111.8×17.5×30
	D4002HB005060	120	40	1.3	1.3	0.6	40±1.0	±1.0	18	111.8×17.5×30
	D3005HB005060	250	30	1.3	1.3	0.6	30±0.7	±1.2	15	168.8×20×45
	D4005HB005060	250	40	1.3	1.3	0.6	40±0.8	±1.3	15	168.8×20×45
	D3008HB005060	400	30	1.3	1.3	0.6	30±0.7	±1.2	15	182.8×25.4×47.5
	D4008HB005060	400	40	1.3	1.3	0.6	40±0.8	±1.3	15	182.8×25.4×47.5
	D3012HB005060	600	30	1.3	1.3	0.6	30±0.7	±1.2	15	182.8×25.4×47.5
	D4012HB005060	600	40	1.3	1.3	0.6	40±0.8	±1.3	15	182.8×25.4×47.5
0.5~8	D3002HB005080	120	30	1.3	1.3	0.7	30±1.0	±1.0	18	111.8×17.5×30
	D4002HB005080	120	40	1.3	1.3	0.7	40±1.0	±1.0	18	111.8×17.5×30
	D3005HB005080	250	30	1.4	1.4	0.7	30±0.8	±1.3	14	168.8×20×45
	D4005HB005080	250	40	1.4	1.4	0.7	40±0.9	±1.4	14	168.8×20×45
	D3008HB005080	400	30	1.4	1.4	0.7	30±0.8	±1.3	14	182.8×25.4×47.5
	D4008HB005080	400	40	1.4	1.4	0.7	40±0.9	±1.4	14	182.8×25.4×47.5
	D3012HB005080	600	30	1.4	1.4	0.7	30±0.8	±1.3	14	182.8×25.4×47.5
	D4012HB005080	600	40	1.4	1.4	0.7	40±0.9	±1.4	14	182.8×25.4×47.5
0.5~18	D3002HB005180	120	30	1.5	1.6	1.0	30±1.2	±1.5	10	168.8×20×45
	D4002HB005180	120	40	1.5	1.6	1.0	40±1.2	±1.7	10	168.8×20×45
	D3005HB005180	250	30	1.5	1.6	1.0	30±1.2	±1.5	10	168.8×20×45
	D4005HB005180	250	40	1.5	1.6	1.0	40±1.2	±1.7	10	168.8×20×45
	D3008HB005180	400	30	1.5	1.6	1.0	30±1.2	±1.5	10	182.8×25.4×47.5
	D4008HB005180	400	40	1.5	1.6	1.0	40±1.2	±1.7	10	182.8×25.4×47.5
0.7~6	D3002HB007060	120	30	1.3	1.3	0.6	30±1.0	±1.0	18	111.8×17.5×30
	D4002HB007060	120	40	1.3	1.3	0.6	40±1.0	±1.0	18	111.8×17.5×30
	D3005HB007060	250	30	1.3	1.3	0.5	30±0.7	±1.1	15	138.3×20×45
	D4005HB007060	250	40	1.3	1.3	0.5	40±0.7	±1.1	15	138.3×20×45
	D3008HB007060	400	30	1.3	1.3	0.5	30±0.7	±1.1	15	152.3×25.4×47.5
	D4008HB007060	400	40	1.3	1.3	0.5	40±0.7	±1.1	15	152.3×25.4×47.5
	D3012HB007060	600	30	1.3	1.3	0.5	30±0.7	±1.1	15	152.3×25.4×47.5
	D4012HB007060	600	40	1.3	1.3	0.5	40±0.7	±1.1	15	152.3×25.4×47.5
0.7~8	D3002HB007080	120	30	1.3	1.3	0.7	30±1.0	±1.0	18	111.8×17.5×30
	D4002HB007080	120	40	1.3	1.3	0.7	40±1.0	±1.0	18	111.8×17.5×30
	D3005HB007080	250	30	1.4	1.4	0.6	30±0.8	±1.2	14	138.3×20×45
	D4005HB007080	250	40	1.4	1.4	0.6	40±0.8	±1.2	14	138.3×20×45
	D3008HB007080	400	30	1.4	1.4	0.6	30±0.8	±1.2	14	152.3×25.4×47.5
	D4008HB007080	400	40	1.4	1.4	0.6	40±0.8	±1.2	14	152.3×25.4×47.5
	D3012HB007080	600	30	1.4	1.4	0.6	30±0.8	±1.2	14	152.3×25.4×47.5
	D4012HB007080	600	40	1.4	1.4	0.6	40±0.8	±1.2	14	152.3×25.4×47.5
0.7~18	D3002HB007180	120	30	1.5	1.6	0.9	30±1.2	±1.4	10	138.3×20×45
	D4002HB007180	120	40	1.5	1.6	0.9	40±1.2	±1.5	10	138.3×20×45
	D3005HB007180	250	30	1.5	1.6	0.9	30±1.2	±1.4	10	138.3×20×45
	D4005HB007180	250	40	1.5	1.6	0.9	40±1.2	±1.5	10	138.3×20×45
	D3008HB007180	400	30	1.5	1.6	0.9	30±1.2	±1.4	10	152.3×25.4×47.5
	D4008HB007180	400	40	1.5	1.6	0.9	40±1.2	±1.5	10	152.3×25.4×47.5


*包含理论耦合损耗




工作频段 (GHz)	型号	额定功率	标称耦合度	主线驻波比	耦合端驻波比	插入损耗*	耦合度	平坦度	方向性	外形尺寸
		Max.(W)	(dB)	Max.(:1)	Max.(:1)	Max.(dB)	Max.(dB)	Max.(dB)	Min.(dB)	(mm)
1~6	D3002HB010060	120	30	1.3	1.3	0.5	30±0.8	±0.7	18	88.9×17.5×30
	D4002HB010060	120	40	1.3	1.3	0.5	40±0.8	±0.7	18	88.9×17.5×30
	D3005HB010060	250	30	1.3	1.3	0.5	30±0.7	±1.1	15	101.6×20×45
	D4005HB010060	250	40	1.3	1.3	0.5	40±0.7	±1.1	15	101.6×20×45
	D3008HB010060	400	30	1.3	1.3	0.5	30±0.7	±1.1	15	115.6×25.4×47.5
	D4008HB010060	400	40	1.3	1.3	0.5	40±0.7	±1.1	15	115.6×25.4×47.5
	D3012HB010060	600	30	1.3	1.3	0.5	30±0.7	±1.1	15	115.6×25.4×47.5
	D4012HB010060	600	40	1.3	1.3	0.5	40±0.7	±1.1	15	115.6×25.4×47.5
1~8	D3002HB010080	120	30	1.3	1.3	0.6	30±0.8	±0.7	18	88.9×17.5×30
	D4002HB010080	120	40	1.3	1.3	0.6	40±0.8	±0.7	18	88.9×17.5×30
	D3005HB010080	250	30	1.4	1.4	0.6	30±0.8	±1.1	14	101.6×20×45
	D4005HB010080	250	40	1.4	1.4	0.6	40±0.8	±1.1	14	101.6×20×45
	D3008HB010080	400	30	1.4	1.4	0.6	30±0.8	±1.1	14	115.6×25.4×47.5
	D4008HB010080	400	40	1.4	1.4	0.6	40±0.8	±1.1	14	115.6×25.4×47.5
	D3012HB010080	600	30	1.4	1.4	0.6	30±0.8	±1.1	14	115.6×25.4×47.5
	D4012HB010080	600	40	1.4	1.4	0.6	40±0.8	±1.1	14	115.6×25.4×47.5
1~18	D3002HB010180	120	30	1.5	1.6	0.8	30±1.2	±1.2	10	101.6×20×45
	D4002HB010180	120	40	1.5	1.6	0.8	40±1.2	±1.2	10	101.6×20×45
	D3005HB010180	250	30	1.5	1.6	0.8	30±1.2	±1.2	10	101.6×20×45
	D4005HB010180	250	40	1.5	1.6	0.8	40±1.2	±1.2	10	101.6×20×45
	D3008HB010180	400	30	1.5	1.6	0.8	30±1.2	±1.2	10	115.6×25.4×47.5
	D4008HB010180	400	40	1.5	1.6	0.6	40±1.2	±1.2	10	115.6×25.4×47.5
2~6	D3002HB020060	120	30	1.3	1.3	0.4	30±0.8	±0.7	18	57.2×17.5×30
	D4002HB020060	120	40	1.3	1.3	0.4	40±0.8	±0.7	18	57.2×17.5×30
	D3005HB020060	250	30	1.3	1.3	0.4	30±0.7	±0.9	15	80.7×20×45
	D4005HB020060	250	40	1.3	1.3	0.4	40±0.7	±0.9	15	80.7×20×45
	D3008HB020060	400	30	1.3	1.3	0.4	30±0.7	±0.9	15	94.7×25.4×47.5
	D4008HB020060	400	40	1.3	1.3	0.4	40±0.7	±0.9	15	94.7×25.4×47.5
	D3012HB020060	600	30	1.3	1.3	0.4	30±0.7	±0.9	15	94.7×25.4×47.5
	D4012HB020060	600	40	1.3	1.3	0.4	40±0.7	±0.9	15	94.7×25.4×47.5
2~8	D3002HB020080	120	30	1.3	1.3	0.5	30±0.8	±0.7	18	57.2×17.5×30
	D4002HB020080	120	40	1.3	1.3	0.5	40±0.8	±0.7	18	57.2×17.5×30
	D3005HB020080	250	30	1.4	1.4	0.4	30±0.8	±0.9	14	80.7×20×45
	D4005HB020080	250	40	1.4	1.4	0.4	40±0.8	±0.9	14	80.7×20×45
	D3008HB020080	400	30	1.4	1.4	0.4	30±0.8	±0.9	14	94.7×25.4×47.5
	D4008HB020080	400	40	1.4	1.4	0.4	40±0.8	±0.9	14	94.7×25.4×47.5
	D3012HB020080	600	30	1.4	1.4	0.4	30±0.8	±0.9	14	94.7×25.4×47.5
	D4012HB020080	600	40	1.4	1.4	0.4	40±0.8	±0.9	14	94.7×25.4×47.5
	D5012HB020080	600	50	1.4	1.4	0.4	50±1.5	±1.2	14	94.7×25.4×47.5
	D3002HB020180	120	30	1.5	1.6	0.6	30±1.0	±1.0	10	80.7×20×45
2~18	D4002HB020180	120	40	1.5	1.6	0.6	40±1.0	±1.0	10	80.7×20×45
	D3005HB020180	250	30	1.5	1.6	0.6	30±1.0	±1.0	10	80.7×20×45
	D4005HB020180	250	40	1.5	1.6	0.6	40±1.0	±1.0	10	80.7×20×45
	D3008HB020180	400	30	1.5	1.6	0.6	30±1.0	±1.0	10	94.7×25.4×47.5
	D4008HB020180	400	40	1.5	1.6	0.6	40±1.0	±1.0	10	94.7×25.4×47.5
	D3012HB020180	600	30	1.5	1.6	0.6	30±1.0	±1.0	10	94.7×25.4×47.5
6~18	D3002HB060180	120	30	1.5	1.6	0.5	30±1.0	±0.9	10	69.7×20×45
	D4002HB060180	120	40	1.5	1.6	0.5	40±1.0	±0.9	10	69.7×20×45
	D3005HB060180	250	30	1.5	1.6	0.5	30±1.0	±0.9	10	69.7×20×45
	D4005HB060180	250	40	1.5	1.6	0.5	40±1.0	±0.9	10	69.7×20×45
	D3008HB060180	400	30	1.5	1.6	0.5	30±1.0	±0.9	10	83.7×25.4×47.5
	D4008HB060180	400	40	1.5	1.6	0.5	40±1.0	±0.9	10	83.7×25.4×47.5

*包含理论耦合损耗

MiCable  **400-918-0388**


福建迈可博电子科技集团股份有限公司

 福建省福州市铜盘路软件大道软件园 A 区 29 栋 5 楼


 www.micable.cn  Sales@micable.cn  0591-87382857



迈可博微信公众号

Mitron  **400-887-3088**

国内销售代理——福州伟博电讯有限公司

 福建省福州市台江区宁化街道望龙二路长汀街 23 号 ICC 升龙环球中心 20 层

 0591-87870001(总部)  www.mitron.cn  Sales@mitron.cn  0591-87870011



伟博电讯微信公众号

北京分公司 | 上海分公司 | 南京分公司 | 武汉分公司 | 成都分公司 | 西安分公司 | 深圳分公司 | 香港分公司
 010-62898691  021-58968955  025-87702131  027-87737881  028-86658422  029-85725769  0755-82870682  852-28081816